

Key Largo Bill of Materials

8 - 4' x 8' sheet 1/2" thick lauan plywood for sides & bottom (3/4 for bottom optional)
6 - 26' long 1/2" x 1-1/2" clear pine (or fir) molding for rub rail, chine log & sheer clamp

You may scarf several shorter pieces together
140 ft - 1 1/2" x 3 1/2" clear fir for frames (random lengths)
21 ft - 1 1/2" x 5 1/2" clear fir for keelson (several pieces scarfed together)
Misc 2x lumber for well (2x10s) or transom motor mount option (2x8s)
170 feet 1 x 4 (3/4 x 3 1/2) clear fir or pine for decking
3/8 plywood and fir 1x2 furring strips for optional seats
12 dozen #6 x 1 1/4" stainless steel wood screws
2 - gallon epoxy
A dozen or so inexpensive disposable paint brushes of various widths
Rubber gloves
Respirators (for sanding dust) & safety glasses
Optional: 50 yds 50" wide light fiberglass cloth (+ additional 2 gallons of Epoxy)

In addition, for the strongback and frame jig, you'll need the following materials:

24' fir 2x6
4 - 8' 4 x 4s
1/2 sheet (2' x 4') 1/2" ply
Handful of 16d box nails
Handful of 5d box nails
Woodworking (or white) glue